## TECHNICAL SPECIFICATION

#### **HEARING PROTECTION**

## Sonis® Compact Helmet Mounted Ear Defenders

Dark Grey / Orange / AEB030-0CY-000



#### DESCRIPTION

The Sonis® range has been stylishly designed with a traffic light colour code for easy identification. Materials have been chosen for both performance and comfort over extended periods of use, with careful design ensuring a small number of key components for easy maintenance.

Sonis®C helmet mounted ear defenders offer medium attenuation

#### OPTIONS

Dark Grey / Orange (AEB030-0CY-000) White / Orange (AEB030-0CC-200)

SAFETY STANDARDS

EN 352-3



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



#### SPECIFICATIONS



Cup Material

Hygiene Hygiene Kits

**JSPCheck** 

Yes



### FEATURES



#### Performance

The Sonis® range of ear defenders have been designed by the JSP R&D team. Working with a leading UK acoustic engineering research facility they have developed an ear defender range that peaks at an unbeaten 37 SNR.



#### Customisation

Sonis® cups can be coloured to meet a corporate identity. They can also be printed with a company logo for improved brand recognition and to discourage theft. MOQ's apply.



APPLICATIONS

#### Hygienic

The headband is manufactured from TPE, making it easy to wipe clean. The sealing rings are easy to replace. Hygiene kits are available for each model.



SNR

Yes

Yes

256g

31 dB

Adjustable

**BSI Kitemark** 

**Product Weight** 

#### Comfort

The over-moulded headband has a built-in comfort area with ventilation. The headband force and the cushion surface area work together to provide optimum cushion pressure and comfort.



#### To facilitate even distribution of pressure the wearer can tilt and adjust the position of the



#### **Universal Compatibility**

earcup for optimum comfort and fit.

**Adjustable Steel Arms** 

The universal slots of JSP helmets allow for easy fitting of Sonis® ear defenders, along with EVOGuard® and Surefit<sup>™</sup> visor systems for maximum protection.

Aerospace	Construction and Infrastructure
Food and Drink Manufacturing	Forestry & Landscaping
Hospitals, Healthcare & Pharmaceuticals	Welding
ACCESSORIES	
Sonis® Compact Hygiene Kit	PPE Cleaning Station, Replacements & Lens Cleaning Wipes
COMPATIBLE PRODUCTS	
EVO®2 Mid Peak OneTouch™ Slip Ratchet Non Vented	EVO®2 Mid Peak OneTouch™ Slip Ratchet Vented
EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented	EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman
EVO®3 Micro Peak OneTouch™ Slip Ratchet Vented	EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



EVO®3 Mid Peak Revolution® Wheel Ratchet Non Vented	EVO®3 Mid Peak OneTouch™ Slip Ratchet Non Vented
EVO®3 Mid Peak OneTouch™ Slip Ratchet Vented	EVO®3 Mid Peak Revolution® Wheel Ratchet Vented
EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented	EVO®5 Olympus® Mid Peak Slip Ratchet Vented
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet	EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented Linesman	EVO® Inter Surefit™ Visor Carrier with 17.5cm Acetate Visor and Long Chinguard
EVO® VISTAlens® Micro Peak Revolution®Wheel Ratchet Non Vented	EVO® VISTAlens® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented
EVO® VISTAlens® Micro Peak Revolution®Wheel Ratchet Linesman	EVO® VISTAlens® Micro Peak Revolution® Wheel Ratchet Vented
EVO® VISTAlens® Micro Peak Revolution®Wheel Ratchet Vented CR2	EVO® VISTAlens® Micro Peak Revolution®Wheel Ratchet Vented Special Badge Holder with Lamp Bracket
EVO® VISTAshield® Micro Peak Revolution® Wheel Ratchet Non Vented	EVO® VISTAshield® DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented
EVO® VISTAshield® Micro Peak Revolution® Wheel Ratchet Vented	EVO® VISTAshield® Micro Peak Revolution® Wheel Ratchet Vented Linesman CR2 Special Badge Holder with Lamp Bracket
EVO® VISTAshield® Micro Peak Revolution® Wheel Ratchet Vented Linesman Special Badge Holder with Lamp Bracket	EVOGuard®M Forestry Helmet Systems
EVOGuard®M Forestry Browguard Systems	EVOLite® Micro Peak OneTouch™ Slip Ratchet Non Vented
EVOLite® Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman	EVOLite® Micro Peak OneTouch™ Slip Ratchet Vented
EVOLite® Micro Peak Revolution® Wheel Ratchet Non Vented	EVOLite® Micro Peak Revolution® Wheel Ratchet Non Vented Linesman
EVOLite® Micro Peak Revolution® Wheel Ratchet Vented	EVOLite® Micro Peak Revolution® Wheel Ratchet Vented Linesman
EVOLite® Mid Peak OneTouch™ Slip Ratchet Non Vented	EVOLite® Mid Peak OneTouch™ Slip Ratchet Vented
EVOLite® Mid Peak Revolution® Wheel Ratchet Non Vented	EVOLite® Mid Peak Revolution® Wheel Ratchet Vented
EVOLite® Skyworker™ Micro Peak Revolution®Wheel Ratchet Vented	Sonis® Compact Hygiene Kit
LOGO	RANGE

Sides

# 

#### VIDEOS

- www.youtube.com/watch?v=kGGYQrImAGk
- www.youtube.com/watch?v=jsG1H-3WQ-U
- www.youtube.com/watch?v=jsG1H-3WQ-U

DOWNLOADS

Image Pack (ZIP)

Declaration of Conformity (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.