



PYRAMEX
Perform At Your Peak™

Ever-Lite® ANSI CE CSA



RUBBER
NOSEPIECE



CO-INJECTED
TEMPLES

Soft nosepiece for snug fit

Semi-frame and slim co-injected temples

Lightweight spectacle – 22 gm

Part No.	Black Frame
ESB8610D ●●●	Clear
ESB8610DT ●●●	AF Clear H2X
ESB8610DTM ●●●	AF Clear H2MAX
ESB8620D ●●●	Gray
ESB8620DT ●●●	AF Gray H2X
ESB8620DTM ●●●	AF Gray H2MAX
ESB8630D ●●●	Amber
ESB8680D ●●●	I/O Mirror
ESB8680DT ●●●	AF I/O Mirror



vimeo.com/pyramex/h2max

There's more to see at
PYRAMEXSAFETY.COM

(P) +44 (0) 1635 254220 | (E) info@pyramexeurope.com

All safety eyewear meets ANSI Z87.1+ standards (●) and provide 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant unless otherwise noted. Some options meet European (EN166) (●) and Canadian (CSA Z94.3) (●) standards.

Ever-Lite®

General Specifications

Weight: 22 gm
 PD: 64 mm
 Bridge: 11.2 mm
 Lens base: 8 curve
 Lens size diagonal: 79.6 mm
 Lens size vertical: 43.3 mm
 Lens thickness: 1.8 mm
 Overall length (lens - tip): 163.5 mm
 Overall width (hinge - hinge): 134.3 mm
 Closest point between temple tips: 70 mm
 Closest point between lens: 11 mm

Materials

Lens: polycarbonate
 Frame: polycarbonate
 Temples: polycarbonate & thermoplastic elastomers (TPE)
 Hinge: polycarbonate
 Screw: stainless steel
 Nosepiece: thermoplastic rubbers (TPR)

Part No.	Lens Markings	Frame Markings
ESB8610D	2 C - 1.2 P 1 F CE	CE P EN166 F
ESB8610DT	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB8610DTM	2 C - 1.2 P 1 F N CE	CE P EN166 F
ESB8620D	5 -2.5 P 1 F CE	CE P EN166 F
ESB8620DT	5 -2.5 P 1 F N CE	CE P EN166 F
ESB8620DTM	5 -2.5 P 1 F N CE	CE P EN166 F
ESB8630D	2 - 1.2 P 1 F CE	CE P EN166 F
ESB8680D	5 -1.7 P 1 F CE	CE P EN166 F
ESB8680DT	5 -1.7 P 1 F N CE	CE P EN166 F

Lens Marking Symbols

Code - field of use

2 or 3: UV filter
 5 or 6: Solar filter

Color perception

C: Unimpaired color perception

Protection class

1.2 - 6: Degree of visible light filtration

Optical class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

Symbols

P: Manufacturer's mark
 N: Filter with anti-fog
 CE: Europe standard

Frame Marking Symbols

Symbols

CE: Europe standard
 P: Manufacturer's mark
 EN166: CE specification for protective eyewear

Mechanical Strength

F: Low energy impact

