

# TECHNICAL DATA SHEET

## 1125 Classic Safety Helmet



### DESCRIPTION

General purpose safety helmet with a 6 point Terylene cradle and Brushed Nylon sweatband.

### SPECIFICATION

	Code	Option	Weight
Product Codes and Helmet Options	S03C*A	Full Peak Slip Non-Vented	362gm
	S03E*F	Full Peak Slip Vented	362gm
	S17*A	Reduced Peak Slip Non-Vented	340gm
Size	51 - 63cm		
Peak	Full (40mm) or Reduced (20mm)		

\* Insert colour code of helmet.



### MATERIALS


Shell	HDPE (High Density Polyethylene)
Cradle	6 Point Terylene webbing
Headband	LDPE (Low Density Polyethylene)
Sweatband	Brushed Nylon with 2mm foam

### COLOURS


	White	Blue	Yellow	Red	Orange	Green
Colour Code	W	B	Y	R	O	G
RAL	9010	5015	1018	3028	2003	6035
Pantone	White	660	108	1795	1505	357

Please note: the closest matching RAL colours are listed.


### CORPORATE BADGING



Front	
	50 x 40mm
	45 x 45mm



Sides	
	100mm
	30mm



Rear	
	100mm
	30mm

## EUROPEAN AND INTERNATIONAL STANDARDS WITH OPTIONS

Product	EN 397:2012 + A1:2012						Options outside the scope of EN 397	EN 50365:2002 (1000V a.c.) For use on low voltage insulations	ANSI/ISEA Z89.1-2009 Type 1			Options outside the scope of ANSI/ISEA	CSA/ CAN Z94.1-05 Type 1		Tested to the performance requirements of AS/NZS 1801:1997 Type 1
	Lateral Deformation (LD)	- 30°C (Low Temperature)	Molten Metal (MM)	440V a.c. (Electrical Resistance)	1000V a.c. (Electrical Resistance)	- 40°C (Low Temperature)			Class C (Conductive 0V a.c.)	Class E (20,000V a.c.)	- 30°C (Low Temperature)		- 40°C (Low Temperature)	Class C (Conductive 0V a.c.)	
Full Peak Slip Non Vented S03C*A		✓	✓	✓	✓				✓						
Full Peak Slip Vented S03E*F		✓													
Reduced Peak Slip Non Vented S17*A		✓	✓	✓	✓				✓						

## ACCESSORIES

Face	S03C*A  compatible with  &  range of Face Protection (carriers and face screens), S17*A compatible with  S03E*F compatible with  clips
Accessory Clips	S565  and S570  clip sets for fitting safety helmet accessories
Ear	Compatible with Centurion helmet mounted Aegean S42C/E/CE and Baltic S41C/E/CE Ear Defenders (supplied with either S570  and/or S565  accessory clips)
Eye	Compatible with S579 Clear Retractable Eyeshield
Sweatband	S31N Brushed Nylon Sweatband
Standard Cradle	S33/3 Terylene Cradle with Brushed Nylon Sweatband
Chinstrap	S30E 2 point elasticated Chinstrap

## PACKAGING AND MAINTENANCE

Packaging	20 per colour, box size 58.7 x 44.7 x 43.7cm. Box weight 8.32kg (Full Peak), 8.04kg (Reduced Peak)
Storage	Can be stored and transported in their original cartons at ambient temperature (0°C to + 30°C) May be stored in the dark for up to 5 years Do not store in direct/high heat or sunlight as this may distort the shell
Lifetime	The Centurion safety helmet has an in-use life of up to 5 years Excessive wear and tear can considerably reduce the lifespan of the product
Cleaning	Clean using warm soapy water and soft cloth
Disposal	Recycling is preferred when possible. Look out for the recycling symbol for material category