

Product Description:

3M Solus 1000 is an adaptable eyewear solution with a range of enhanced comfort features. The spectacle is available with a 3M™ Scotchgard™ Anti-Fog Coating which provides scratch resistance and resists fogging for longer than traditional anti-fog coatings.

Intended Use:

These products are intended for protection against high speed particles at low energy (F) at extremes of temperature -5°C and +55°C (T) in accordance with EN166:2001. In addition, options are available that protect against UV radiation in accordance with EN170:2002 or Sunglare in accordance with EN172:2001

Key Features:

- Optical class 1 lens suitable for prolonged use
- 3M Scotchgard anti-fog coating provides superior anti-fog properties, outperforming the N marking requirements of EN166.
- 3M Scotchgard anti-fog coating provides scratch resistance and durability, complying with the K marking requirements of EN166.
- Coating retains its effectiveness for at least 25 washes. Can be disinfected with diluted bleach soaking or alcohol wipes without losing its anti-fog performance.
- Offers excellent protection against UV radiation.
- Designed with an optional foam-lined insert to help limit exposure to nuisance dust. The insert features small vents to help reduce fogging.
- Designed with removable temple arms to allow attachment of optional elastic headband.

Applications:

These products can be used in a wide range of applications including:

- Manufacturing
- Metal working
- Mining/Oil & Gas
- Construction/outdoors
- Food industry

Standards and Approval:

The 3M[™] Solus[™] 1000 Series has been shown to meet the basic safety requirements under Article 10 of the European Community Directive 89/686/EEC and is thus CE marked.

These products have been examined at the design stage by ECS GmbH – European Certification Service, Huettfeldstrasse 50, 73430 Aalen Germany (Notified body number 1883).

These products are tested and CE approved against EN166:2001.



Marking:

3M™ Solus™ 1000 Series Safety Eyewear complies with the requirements of EN 166:2001 and associated standards and bears the following marks:

Lens marking

2C-1.2 3M 1 FT K N CE

Clear Polycarbonate Amber Polycarbonate 2C-1.2 3M 1 FT K N CE Grey Polycarbonate

5-3.13M1FTKNCE

Frame marking

3M EN166 FT CE

Explanation of Marking

Marking	Description
2C-1.2 (EN 170:2002)	UV protection with good colour recognition.
	This product conforms to the requirements of the standard, providing UV protection for the complete specified range (210nm – 365nm).
5-3.1 (EN 172:1994 (as amended))	Sun-glare protection conforming to the requirements of the standard, providing UV protection for the complete specified range (280nm – 350nm).
1	Optical class
F	Impact protection against high speed particles at low energy (45m/s)
Т	Tested for impact protection at extreme temperature conditions -5°C and +55°C
K	Resistance to surface damage by fine particles
N	Resistance to fogging

Materials listing:

Component	Material
Lens	Polycarbonate
Frame (rigid)	Polycarbonate
Frame (soft)	TPE
Insert	Nylon / EVA Foam
Nosepiece	TPR
Headband	Nylon
Headband connector	Polycarbonate
Weight	With arms: 25g With strap: 29g Foam insert (standalone): 10g

Use limitation

- Never modify or alter this product.
- Do not use this product against hazards other than those specified in this document.
- These products are not suitable for welding.
- This product is NOT designed to be worn over prescription spectacles.

Personal Safety Division 3M United Kingdom plc 3M Centre Cain Road, Bracknell Berkshire RG12 8HT t: 0870 60 800 60 www.3M.co.uk

3M Ireland Limited The Iveagh Building The Park, Carrickmines Dublin 18 t: 01 280 3555 f: 01 280 3509

Please recycle. Printed in the UK. 3M and Scotchgard are trademarks of the 3M Company. © 3M 2016. All rights reserved. J319677

