TECHNICAL SPECIFICATION



EYE AND FACE PROTECTION

EVOGuard®C4-MAX Industrial Visor

EVOGuard®C4-MAX / ADA270-070-000



DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and EVO® helmet range, the C4-MAX visor offers up to AT rated impact protection and features an integral chinguard for added coverage.

OPTIONS

EVOGuard®C4-MAX (ADA270-070-000)

SAFETY STANDARDS

EN 166 • EN 170





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacturer's Trademark

JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection for face shields

A - When Fitted to EVO® Helmet



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Τ



Resistance to Molten Metals and Hot Solids (optional)



Resistance to fogging (optional) Ν



BSI Kitemark Yes



Product Weight

220g



Supplied With: EVO® 2,3,5,DS,Lite,Skyworker™ Arms. EVO8/EVOLite Badgeholder Arms. **EVOGuard® Browguard Mounting System**



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use)



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.

B - When Fitted To EVOGuard® Browguard



Protection from Liquid Splash

3



Resistance to Surface Damage by Fine Particles (optional)

K



Visor Length

21.5cm

Material

Polycarbonate Shield



Recyclable

Yes

FEATURES



Helmet & Browguard Integration

Fully compatible with EVO® helmet and the EVOGuard® Browguard system. Not including EVO®Vista® or EVO®6100 ranges



Vision

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinguard.



Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



Impact

Five high performance visors offering up to A rated impact resistance when fitted to a safety helmet and fully compatible with EVOGuard® browguard for medium energy impact protection.



UV Protection

Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.

APPLICATIONS

Aerospace Agricultural

Construction and Infrastructure Facilities Management

Food and Drink Manufacturing Manufacturing





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

 $Do \ Not \ Publish \ without \ written \ permission \ from \ JSP \ Limited. \ Contact \ copyright@jspsafety.com. \ Information \ correct in the \ United \ Kingdom \ at \ Not \ Publish \ without \ written \ permission \ from \ JSP \ Limited.$ date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





Mining, Aggregates and Quarrying	Rail and Tunnelling
Scaffolding and Roofing	Utilities Contractors

ACCESSORIES

PPE Cleaning Station, Replacements & Lens Cleaning Wipes

COMPATIBLE PRODUCTS	
EVO®2 Mid Peak OneTouch™ Slip Ratchet Non Vented	EVO®2 Mid Peak OneTouch™ Slip Ratchet Vented
EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented	EVO®3 Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman
EVO®3 Micro Peak OneTouch™ Slip Ratchet Vented	EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented
EVO®3 Micro Peak Revolution® Wheel Ratchet Non Vented Linesman	EVO®3 Micro Peak Revolution® Wheel Ratchet Vented
EVO®3 Mid Peak Revolution® Wheel Ratchet Non Vented	EVO®3 Mid Peak OneTouch™ Slip Ratchet Non Vented
EVO®3 Mid Peak OneTouch™ Slip Ratchet Vented	EVO®3 Mid Peak Revolution® Wheel Ratchet Vented
EVO®5 DualSwitch™ Micro Peak Revolution® Wheel Ratchet Vented	EVO®5 Olympus® Mid Peak Slip Ratchet Vented
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet	EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented
EVO®5 Olympus® Mid Peak Revolution® Wheel Ratchet Vented Linesman	EVO®8 Mid Peak Wheel Ratchet Non Vented
EVO®8 Mid Peak Wheel Ratchet Non Vented Linesman	EVO®8 Mid Peak Wheel Ratchet Vented
EVOLite® Micro Peak OneTouch™ Slip Ratchet Non Vented	EVOLite® Micro Peak OneTouch™ Slip Ratchet Non Vented Linesman
EVOLite® Micro Peak OneTouch™ Slip Ratchet Vented	EVOLite® Micro Peak Revolution® Wheel Ratchet Non Vented
EVOLite® Micro Peak Revolution® Wheel Ratchet Non Vented Linesman	EVOLite® Micro Peak Revolution® Wheel Ratchet Vented
EVOLite® Micro Peak Revolution® Wheel Ratchet Vented Linesman	EVOLite® Mid Peak OneTouch™ Slip Ratchet Non Vented
EVOLite® Mid Peak OneTouch™ Slip Ratchet Vented	EVOLite® Mid Peak Revolution® Wheel Ratchet Non Vented
EVOLite® Mid Peak Revolution® Wheel Ratchet Vented	EVOLite® Skyworker™ Micro Peak Revolution®Wheel Ratchet Vented
Sonis® Compact Helmet Mounted Ear Defenders	Sonis®1 Helmet Mounted Ear Defenders
Sonis®3 Helmet Mounted Ear Defenders	

RANGE VIDEOS



www.youtube.com/watch?v=_VnTgBRRT9E

DOWNLOADS



Declaration of Conformity (PDF)







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





