


# STYLE REF: VX950A

## STYLE NAME: ONYX BLACK



# Rock Fall®

INNOVATION IN SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S3 HI WR HRO SRC | SIZE UK 3-8 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, DESIGNED TO FIT A LADIES FOOT, ACTIV-TEX WATERPROOF MEMBRANE, SOLID RUBBER OUTSOLE

# VX950A



CLICK A FEATURE OR COMPONENT TO LEARN MORE



100%  
Non  
Metallic



Anti  
Static



Heat  
Resistant  
to 300°C



HI Resistant  
to 150°C



Oil  
Resistant



Protective  
Midsole



Protective  
Toecap



Small  
Sizes  
Available



Water  
Repellent  
Upper



Waterproof  
Membrane



Ladies  
Fit



Highest Level  
Slip Resistance

ACTIV-TEX

### Upper Materials

Genuine Full Grain Waxy Smooth Leather

### Lining Materials

Activ-Tex Waterproof Membrane

### Outsole

Solid Rubber

### Footbed

EVA Footbed

### Internal Toecap

Fibreglass

### Internal Midsole

Composite

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/03/2016

[WWW.ROCKFALL.CO.UK](http://WWW.ROCKFALL.CO.UK) | [WWW.ROCKFALL.CO.UK/PRODUCTS/ONYX-BLACK](http://WWW.ROCKFALL.CO.UK/PRODUCTS/ONYX-BLACK)

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

**EC DECLARATION OF CONFORMITY**



**Head Office & Distribution Centre**

Rock Fall UK Limited  
Unit 1 Major House  
Wimsey Way  
Alfreton, Derbyshire  
England. DE55 4LS

E: [sales@rockfall.co.uk](mailto:sales@rockfall.co.uk)  
T: 01773 608616

[www.rockfall.co.uk](http://www.rockfall.co.uk)

The manufacturer or his nominated representative established in the community;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Declares that the PPE described hereafter;

**VIXEN ONYX VX950A**

Is in conformity with the provisions of Council Directive 89/686/EEC and, where such is the case, with the national standard transposing harmonised standard no. EN ISO 20345:2011 (for the PPE referred to in Article 8(2))

This declaration of conformity is issued under the sole responsibility of the manufacturer;

**ROCK FALL UK LTD  
MAJOR HOUSE, UNIT 1  
WIMSEY WAY  
ALFRETON  
DERBYSHIRE, DE55 4LS  
UNITED KINGDOM**

Is identical to the PPE which is subject of EC certificate No **LECFI00339188** Issued by:-

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**

Is subject to the procedure set out in Article 11 point A or point B of the Directive 89/686/EEC under the supervision of the notified body:

**ITS TESTING SERVICES (UK) LTD  
CENTRE COURT  
MERIDIAN BUSINESS PARK  
LEICESTER  
LE19 1WD**


Signature:

Position: Director

Date: 01/01/2017



# EC Type Examination Certificate



### Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.  
Centre Court  
Meridian Business Park  
Leicester, LE19 1WD  
United Kingdom  
Phone: +44 (0)116 263 0330  
Fax: +44 (0)116 263 0311



www.intertek.com

<b>Issued to</b>	: Rock Fall UK Ltd Wimsey Way, Alfreton Trading Estate, Derbyshire UK DE55 4LS	
<b>Manufacturer</b>	: [Faded text]	
<b>Date of Issue</b>	: 25 March 2014	
<b>Expiry Date</b>	: 19 November 2017	
<b>Certificate No.</b>	: LEC FI00339188 (Extension to certificate LEC FI00331203)	
<b>Product Reference(s)</b>	: VX950A, VX950C	
<b>Description</b>	: Construction	: Cemented
	: Toecap	: PEP# Composite
	: Midsole	: PEP# Composite
	: Last	: #PEP-PL
	: Sole	: PS-2061# RB
	: Test Report(s)	: See Technical File
	: Size Range	: UK 5 – 13
	: Category	: S3 WR HRO SRC

*M. [Signature]*

Assessor

25/03/2014

Date

*P. Williams*

Certification Manager


25/03/2014

Date

For and on behalf of **ITS Testing Services (UK) Limited**

Registered In England No. 1408264 Registered Office: Academy Place, 1-9 Brook Street, Brentwood, Essex. CM14 5NQ

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



Number: GZHT90492559

**Test Report**

Tests Conducted (As Requested By The Applicant)

Slip Resistance (EN ISO 20344:2011(5.11) & ISO 13287:2012, SRA, Temperature: 23°C)

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 36</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.33	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.34	Min. 0.32	Pass
<u>Size 42</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.34	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.35	Min. 0.32	Pass
<u>Size 47</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.35	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.35	Min. 0.32	Pass

**Note:**

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

**Remark:**

- #1 = Using Standard Shoemaking Last
- #2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.

*This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.*



中国认可  
国际互认  
检测  
TESTING  
CNAS L0220

Number: GZHT90593751

**Test Report**

Tests Conducted (As Requested By The Applicant)

6 Slip Resistance (EN ISO 20344:2011(5.11) & ISO 13287:2012, SRB, Temperature: 23°C)

Sample	Size	Test Floor	Lubricant	Modes	Results	Requirement	Pass/Fail
-	36 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.16	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.23	Min. 0.18	Pass
	42 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.18	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.23	Min. 0.18	Pass
	47 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.19	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.25	Min. 0.18	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark: #1 = Using Standard Shoemaking Last  
#2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.