

STYLE REF: RF115

STYLE NAME: BANTAM

Rock Fall[®]
INDUSTRY DEFINING SAFETY FOOTWEAR

SPECIFICATION: EN ISO 20345:2011 S1P SRC | SIZE: UK 3-13 | COLOUR: BLACK

100% NON-METALLIC, WITH PROTECTIVE TOECAP AND MIDSOLE, BANTAM IS COMFORTABLE AND LIGHTWEIGHT, IT'S DEVELOPED WITH INNOVATIVE COMFORT MATERIALS INCLUDING NYLON AND 3D PRINTED UPPER, A SHOCK ABSORBING DUAL DENSITY EVA NITRILE RUBBER OUTSOLE AND ACTIV-STEP[®] PU ANTI-FATIGUE COMFORT FOOTBED.

RF115



Upper Material

Breathable nylon with 3D printed styling

Protective Components

Protective fibreglass toecap and composite anti-penetration flexi-midsole

Lining Materials

Moisture wicking breathable mesh fabric lining

Scuff Cap and Outsole

Shock absorbing dual density EVA nitrile rubber outsole

Footbed

Activ-Step[®] PU anti-fatigue comfort footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/04/2020

WWW.ROCKFALL.COM | WWW.ROCKFALL.COM/PRODUCTS/BANTAM

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS



Issued to:

Rock Fall UK Ltd
Major House
Unit 1/3 Wimsey Way
Alfreton
Derbyshire
DE55 4LS
UK

Notified Body: 2777

SATRA customer number: P1769

EU Type-Examination Certificate

Certificate number: 2777/15498-01/E00-00

This EU Type-Examination Certificate covers the following product group(s) supported by testing to the relevant standards/technical specifications and examination of the technical file documentation:

Following the EU Type-Examination this product group has been shown to satisfy the applicable essential health and safety requirements of Annex II of the PPE Regulation (EU) 2016/425 as a Category II product.

Product reference:	Description:
Rock Fall RF108 Fly	Safety trainer comprising honey leather upper with synthetic linings. 5 eyelets comprise the laced fastening system. Composite toe cap, non-metallic perforation resistant insert and a cemented rubber outsole.
Rock Fall RF115 Bantam	Ankle safety boot comprising honey leather upper with synthetic linings. 5 eyelets comprise the laced fastening system. Composite toe cap, non-metallic perforation resistant insert and a cemented rubber outsole.

Classification:

EN ISO 20345:2011 S1 P SRC

Size Range: 35 – 48 EUR

Standards/Technical specifications applied:
EN ISO 20345: 2011

Technical reports/Approval documents:
Intertek: GZHT90775582, GZHT90773848, GZHT90767155, GZHT90861308, GZHT90681181, GZHT90711809(S1), GZHT90738287, GZHT90762937, GZHT90890696, GZHT90601628

Signed on behalf of SATRA:

Hannah Coe

Geoff Graham

Date first issued: 17/12/2020
Date of issue: 17/12/2020

Expiry date: 17/12/2025

EU DECLARATION OF CONFORMITY

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ROCK FALL RF115 Bantam Lightweight Safety Trainer

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2011**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P. Republic of Ireland. Approved Body 2777** who performed the Eu type examination (Module B) and issued the EU type -examination certificate: **2777/15498-01/E00-00**

The PPE is subject to the procedure set out in **Module C** of the PPE Regulation EU 2016/425 under the supervision of the notified body:

SATRA Technology Europe Ltd, Bracetown Business Park, Clonee, D15YN2P. Republic of Ireland. Approved Body 2777

Signature:

A handwritten signature in black ink, appearing to read "R. K. Wilson".

Position: Director

Date: 18/12/2020