

Material Safety Data Sheet

MaxiCut® Oil™ 44-305

General description

MaxiCut® Oil™ combines cut protection with comfort, flexibility and dexterity for oily and wet environments.

Compliances

ATG®, hereby declares, that this PPE Type is in conformity with the relevant Union harmonisation legislation: Regulation (EU) 2016/425 and the relevant harmonized standards (EN) EN 420: 2003 + A1: 2009, EN 388: 2016, EN 407: 2004.

Use

Cut resistant work glove for Assured Protection™ in oily or wet environments.
For detailed applications where this product can be used please consult the ATG® website at <http://www.atg-glovesolutions.com>.

Main ingredients

Coating: NBR (Nitrile Butadiene Rubber)

Liner: UHMWPE-Glass-Nylon, Polyester, Spandex

Hazardous ingredients

REACH

All ingredients used in the manufacturing and construction of this product are compliant with the EU directive for the "Regulation of chemicals and their safe use" more commonly known as REACH -- EU directive EC1907/2006. REACH stands for "Registration, Evaluation, Authorisation and Restrictions of CHEMical substances". The key aim of REACH is to provide high levels of protection to human health and the environment. More information can be found at:

http://ec.europa.eu/environment/chemicals/reach/reach_intro.htm.

Oeko-Tex®

This product has been tested and successfully passed the Oeko-Tex® Standard 100 global standard which indicates that the product is skin friendly. Look for the Oeko-Tex® logo to make sure you are buying a skin safe product. For more information on Oeko-Tex® please visit http://www.oekotex.com/oekotex100_public/index.asp?cls=02.

Precautions for use

Before usage, inspect the glove for any defects or imperfections. If a glove is ripped or punctured during use dispose them immediately. Wear an appropriate size and do not wear gloves that are too tight or too loose.

Storage requirements

Store in a cool; dry place which is away from direct sunlight and/or heat. Extended exposure to direct sunlight or excessive heat will reduce shelf life and resulting in fading, discoloration and cracking. Normal anticipated shelf life is 5 years.

Disposal

After the glove has been used it may be contaminated with infectious or other hazardous materials. Please dispose according to local authority regulations.



Material Safety Data Sheet

MaxiCut® Oil™ 44-305

Fire notes

Gloves will decompose at high temperatures. Extinguish using water, CO2 spray or dry powder.

First aid

Remove contaminated gloves. Skin contact: if an allergenic reaction occurs seek medical advice immediately. Eye contact; rinse thoroughly with low pressure water. If any prolonged discomfort, seek medical advice immediately.

Issue date: 08.07.2019

