≤н⊂ша. **305**

LATEX COATED PALM AND KNUCKLES; FOR INTENSE MANUAL HANDLING

Reinforced 3/4 latex coating protects the hand and provides excellent mechanical resistance.

FEATURES

- A flexible, soft glove that absorbs perspiration, for ultra-comfortable extended wear and with good mechanical resistance.
- > Enhanced protection to the knuckles and back of hand
- Rough finish to the latex provides tactile feel and better grip
- > Antibacterial and anti-odour treatment
- > Ergonomic fit
- > Seamless liner prevents irritation
- > Designed for easy movement and continuous wear





3/4 COATING

Typical Industries

- Construction
- Forestry & Fishing
- Municipal Services
- Rail
- Utilities

- Suitable Applications
- Cement Work
- Masonry
- Plastering
- Roofing
- Stonework
- Waste Management

CERTIFICATION



EN 388:2016



See overleaf for explanation





DURABL LATEX GRIP



showa. **305**

PRODUCT INFORMATION

	MATERIALS	LINER:	10 gauge cotton, polyester
		COATING:	Natural Latex
	COLOUR	Grey/blue	
	LENGTH (mm)	250 (size dependent)	
	CUFF STYLE	LE Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL	SHO3051 SHO3052 SHO3053 SHO3054	10 pairs per pack 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal, electrical, chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE : Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS* 0-4 0-5 0-4 0-4 A-F P

Limpact Resistance Straight Blade Cut Resistance (EN ISO: 13997) Puncture Resistance Tear Resistance Circular Blade Cut Resistance

Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- **F:** +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2020 Globus (Shetland) Ltd | SHO-DATA-305_0620_1

EU compliance certificate delivered by the notified body SGS Fimko Oy, Särkiniementie 3, Helsinki, 00211, Finland (Notified Body number 0598)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.